



APPROXIMATE QUANTITIES

1. 12" DIA. 1' LONG	880
2. 12" DIA. 1' LONG	400
3. 12" DIA. 1' LONG	100
4. 12" DIA. 1' LONG	100
5. 12" DIA. 1' LONG	100
6. 12" DIA. 1' LONG	100
7. 12" DIA. 1' LONG	100
8. 12" DIA. 1' LONG	100
9. 12" DIA. 1' LONG	100
10. 12" DIA. 1' LONG	100
11. 12" DIA. 1' LONG	100
12. 12" DIA. 1' LONG	100
13. 12" DIA. 1' LONG	100
14. 12" DIA. 1' LONG	100
15. 12" DIA. 1' LONG	100
16. 12" DIA. 1' LONG	100
17. 12" DIA. 1' LONG	100
18. 12" DIA. 1' LONG	100
19. 12" DIA. 1' LONG	100
20. 12" DIA. 1' LONG	100

GENERAL NOTES:

- All work indicated on this plan shall be done in accordance with applicable provisions of the San Francisco Public Works Ordinance.
- All sewer lines shall be constructed of vitrified clay pipe with manholes and receiving chambers of concrete.
- Manholes shall be constructed of concrete with a minimum diameter of 36 inches.
- Receiving chambers shall be constructed of concrete with a minimum diameter of 36 inches.
- Concrete curbs shall be constructed of concrete with a minimum height of 6 inches.
- Gravel bedding shall be constructed of gravel with a minimum depth of 4 inches.
- Trenches shall be constructed of concrete with a minimum width of 36 inches.
- Excavations shall be shored and braced in accordance with applicable provisions of the San Francisco Public Works Ordinance.
- Excavations shall be backfilled with approved material.
- Excavations shall be covered with a minimum height of 6 inches.
- Excavations shall be covered with a minimum width of 36 inches.

NESTE & BRUDIN
 CIVIL ENGINEERS
 187 WEST FIFTH ST.
 SAN FRANCISCO, CALIF.

DEPARTMENT OF ENGINEERING
 CITY OF SAN FRANCISCO
IMPROVEMENT PLAN - PARKING AVENUE
 DEBISHING AVENUE
 900' NORTH OF 50th ST.
 DRAWING NO. 3036
 SHEET 1 OF 1