



- GENERAL**
- All work indicated on these plans shall conform to the provisions of specifications and standards of the City of San Bernardino.
 - All sewer connections shall be made on an upward grade of Two per cent and shall extend from the property line.
 - 24" pipes with 4" manholes shall be shown in this plan.
 - All these connections shall be shown in the field.
 - Standard Manhole Type and Cover shall be as shown in the City of San Bernardino Department of Public Works Drawing No. 232.
 - No more than 2000 ft. shall be open at one time. Open trench shall be protected with trench shields, backfilled, compacted and protected with a paved street surface.
 - Branch Street El. 1170.00 at Atchison Street.
 - Contractor shall verify the location of all existing manholes and shall verify or ascertain the location of all utilities and be responsible for all damage caused by his operations.
 - Manhole steps shall be installed. Covers shall be aluminum foundry type or approved equal.
 - V.C.P. shall be used where shown on these plans.
 - These connections shall be with pipe, cast iron pipe, or asbestos pipe joints shall be WEDGED-LOCK BAND-SEAL, CERAMIC-WELD, or joints shall be Orlon and that Asbestos cement pipe joints shall be type using natural rubber gaskets.



Scale 1" = 40'

DEPARTMENT OF ENGINEERING
CITY OF SAN BERNARDINO
 TAMARISK AVENUE Between Arrow Road and Oregon Street
 EUCALYPTUS AVENUE Between Arrow Road and Oregon Street
 SUBMITTED BY: *Robert J. Tiller*
 APPROVED: *August 14, 1938*
Charles C. Wolf
 CITY ENGINEER
 REGISTERED CIVIL ENGINEER